


TK4M Svetsmutter Obeh

Fyrkant svetsmutter med 4 svetspunkter

DIN 928, Stål (max. C=0,25%)

Square weld nuts, 4 weld projections steel, plain



d	e _{min}	h ±0,1	m h14	s h14	Pris/100 st PGR 1707 Obeh	04.04 Förp
M4	9	0,6	3,5	7	284:— ¹	1000
M5	12	0,8	4,2	9	254:—	1000
M6	13	0,8	5	10	94:—	1000
M8	18	1,0	6,5	14	148:—	1000
M10	22	1,2	8	17	284:—	500
M10 x 1,25	25	1,2	8	17	795:— ²	500
M12	25	1,4	9,5	19	1180:—	200
M14	28	1,4	11	22	1770:—	200


Art. nr ¹ 9 28 00 -- 4
² 9 28 00 _10 125

FK4M Svetsmutter, typ H, Obeh

Fyrkant svetsmutter med hals, typ H

Stål, klass 8

Square weld nuts type H steel, plain



d	s	e _{min}	b _r	m TOL h14	c TOL ±0,1	Pris/100 st PGR 1707 Obeh	04.04 Förp
M6	10	13	1,2 ±0,15	5,0	0,6	260:—	5000
M8	14	18	1,5 ±0,15	6,5	0,8	480:—	2000
M10	17	22	1,8 ±0,2	8,0	1,0	765:—	1000
M12	19	25	2,0 ±0,2	9,5	1,2	1380:—	100


Art. nr 9 0 79 0H -- 6

FK4M Svetsmutter Obeh

Fyrkant svetsmutter med hals

Stål, klass 8 *

Square weld nuts steel, plain



d	s	e	d _e	d ₂	m js14	h ₂ ±0,15	c ±0,15	Pris/100 st PGR 1707 Obeh	04.04 Förp
M6	12,7	15,9	9,53	7,75	5,6	1,6	0,4	390:—	1000
M8	14,28	16,7	11,91	10,46	6,4	1,6	0,4	585:—	1000
M10	15,88	19,0	14,28	12,57	7,9	1,6	0,4	1140:—	500
M12	20,64	25,4	17,37	13,2	11,1	1,6	0,4	1580:—	200

*M4 och M5 ersätts med DIN 928 eller FK4M Typ H, se ovan.

Art. nr 9 0 79 00 -- 6